V7 S20PD
Entertainment Line

Specifications

Panel Size	20.1" (~ 510 mm)
Viewable Size	4:3 (~ 408 x 306 mm)
Panel Specification	CMO Panel, TN
Recommended Resolution	1400 x 1050
Pixel Pitch	0.2916 mm
Colours max.	16.2 Mio
Brightness typ.	300 cd/m²
Contrast Ratio typ.	600:1
Viewing Angle H/V	150°/130°
Response Time typ.	8 (2/6) ms
Features	Speakers (2x 2,5 W), Kensington® Security Port, internal power supply
Adjustment	Bightness, Contrast, Auto-Adjust, Clock, Phase, H/V-Position, Sharpness, Colour Control, OSD Position, Audio Control, Language, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 75 Hz 1440 x 1050 @ 60 hz
Horizontal Frequency	30 - 82 kHz
Vertical Frequency	56 - 76 Hz
Videobandwidth	140 Mhz
Input Signal	RGB Analog
Input Terminal	15pin D-Sub
Plug & Play	DDC2B
Power Management	VESA DPMS, ENERGY STAR
Power Consumption On/Off	55/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
Dimensions WxHxD **with stand** **without stand** **packaging**	 464 x 437 x 232 mm 467 x 385 x 60 mm 525 x 490 x 140 mm
Weight with stand **incl. packaging**	5.3 kg 6.43 kg
Tilt	20° ~ -5°
Operating/Storage Temperature	5-35/-20-55°C, Humidity: 20-80/20-85%
Wallmountable	VESA 75 x 75 mm
Certifications & Standards	CE, TUV/GS, FCC, UL, TCO 03, ISO 13406-2
Supplied Accessories	12 languages manual CD-Rom, quick guide, power cable, VGA cable, audio cable
Pixel Criteria	bright <= 3, dark <= 3, total <= 7
Service	3 years on-site

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions are disclaimed. Measurement standards and testing conditions as per manufacturer definitions, available on request.
Issue: 02/2006